



健隆投資有限公司
STRONG BASE INVESTMENT LTD.

Unit 17, 11/F., Hewlett Centre, 52-54 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong.
 Tel: (852) 2793 3293 Fax: (852) 2793 3096



Approval Sheet
(確認書)

編號 Ref. No.	110719-02
日期 Issued Date	2011-7-19

公司名稱 : _____
 Company Name

產品編號 : E1-3036AUR1
 Part No.

產品種類 : 数码显示板
 Category

產品描述 : 0.36 Inch、超高亮红光、三位、共阳、灰面白字
 Description

客戶產品編號 : _____
 Customer No.

備注 : _____
 Remarks

STRONG BASE			
ISSUER	APPROVER	CHECKER	ENGINEER
	曾雪昭	刘根秀	何春宁

Authorized Signature 客戶簽字				
部門 Department				
簽字 Signature				

工廠名稱:宇之亮電子(深圳)有限公司

工廠地址:廣東省深圳市龍崗區橫崗鎮荷坳村金源工業區

Company Name: Pretty Light (Shen Zhen) Limited

Factory Address:jin-Yuan,Industrial Zone He-Ao Cun,Heng-Gang
 Zhen Long-Gang Area,Shen-Zhen City,

TEL: (755) 8976 6931 2862 5421

FAX: (755) 28684819 2862 5922



健隆投資有限公司

STRONG BASE INVESTMENT LTD.

Unit 17, 11/F., Hewlett Centre, 52-54 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong.

Tel: (852) 2793 3293 Fax: (852) 2793 3096



PART No: E1-3036AUR1

Client:

Single Chip Light Electricity Characteristic Data

※Absolute Maximum Ratings at Ta=25°C

Parameter	Rating	Unit
Power Dissipation Per Chip	50	mW
Perk Forward Current Per Chip (Frequency 10KHz, 1/10Duty Cycle)	60	mA
Reverse Voltage Per Chip	5	V
Operating Temperature Range	-20~+65	°C
Storage Temperature Range	-20~+65	°C
Storage Humidity	45% ~ 85%	

※Electrical and Optical Characteristics at Ta=25°C

Parameter	Symbol	Condition	Color	Min	Typ	Max	Unit
Forward Voltage Per Chip	VF	IF=20mA	Red	1.7	2.0	2.5	v
Reverse Current	IR	VR=5V	-	-	-	50	uA
Luminous Intensity Per Chip	IV	IF=20mA	Red	20	30	40	mcd
Dominant Wave Length	λd	IF=20mA	Red	625	630	640	nm
Normal Forward Current	IF		All Color	5	10	20	mA

Note : Soldering Bath : not more than 4 seconds @260°C。 The bottom ends of plastic reflector should be at least 2mm above the solder surface。


Soldering Iron : not more than 3 seconds @300°C under 30W。



PART No.: E1-3036AUR1

Client:

PACKAGE DIMENSION(Unit: mm Tolerance: ± 0.25)



INTERNAL CIRCUIT DIAGRAM

Pin Function

